

								AWARD			
Line #	High Pressure Washer with Gasoline Engine			Advanced Cleaning Equipment, Inc.		Easy Klean Pressure Systems Ltd.		Hotsy Equipment Co.		Southern Carlson	
	Description	Qty	UOM	Unit Price	Ext. Price	Unit Price	Ext. Price	Unit Price	Ext. Price	Unit Price	Ext. Price
1	High Pressure Washer with Gasoline Engine	7	EA	\$ 4,050.00	\$ 28,350.00	\$ 3,790.00	\$ 26,530.00	\$ 3,890.00	\$ 27,230.00	\$ 3,944.00	\$ 27,608.00
<b>Total</b>				<b>\$ 4,050.00</b>	<b>\$ 28,350.00</b>	<b>\$ 3,790.00</b>	<b>\$ 26,530.00</b>	<b>\$ 3,890.00</b>	<b>\$ 27,230.00</b>	<b>\$ 3,944.00</b>	<b>\$ 27,608.00</b>
Payment Terms				5 10		None None		0 10			
Delivery Days ARO				30				20		14	
Comments				VI. C. 3. 1.53 gal Honda GX390 clears CARD & EPA emission regulations E. 1. 6 gal F. Hose is steel double braid type meeting SAE100R2 and rated at 4500 PSI. at 275(degrees)F. I. 4. #4. Safety Flow Switch J. 1. A. 112 B. 112 OSHA required hearing protection stickers L. 4. Black & Yellow W. Manufacturer's Warranty is attached. Lifetime warranty on brass manifold will be honored.		VI. C. 3. 1.95 Gallons 5. Machine on 4 Rubber tires D. 2. 4,000 PSI E. 1. 10 Gallon F. 1. A. 4000 PSI 3. 0,15,25,40 degree included. 4. B. Not Required 5. Not Required J. 1. A. 98.7 B. 93.4 K. 4. Can be found online L. 1. None Required 4. Orange		1065ssE Hotsy Washer VI. C. 3. 1.7 E. 1. 8 GALLONS J. 1. A. 100 DECIBELS B. 98 DECIBELS L. 4. RED		VI. C. 3. 1.6 Gallon D. Pump Delivers 4.0 Gallons per minute pressure adjustable from 600 psi to 4200 psi E. 1. 8 Gallons H. 4. All stainless steel frame No powder coat. Frame is constructed of superior medical grade stainless steel. J. 1. Meets industry standards A. Meets industry standards B. Meets industry standards I do not have access to these readings but can be made available prior to awarding if necessary. L. 4. Stainless Steel W. 4. 10 year warranty 5. 10 year warranty Pump has 10 year warranty Coil has 10 year warranty	

**Invalid Bid**  
Interline Brands, Inc.

Award Justification: Apparent low bidder did not meet Specification VI, C. 5. Engine to be mounted on rubber mounts to reduce vibrations.