

State of Nebraska
 Technical Specification Sheet
 6914 OF Attachment A 1.0

States Description

Knuckle Boom Crane and Bed

Contractors Description

State Specifications		Meets Spec Yes No		Contractor Specification
1	See Attachments B- E for various Specifications and visual examples.			
2	See Attachment B for Vehicle Specifications that the Custom Flat bed with Hydraulic Loader will be installed on.			
3	Custom Flatbed with Headache Rack			
	a- Black Powder Coated or approved equivalent			
	b- Minimum 96 Inch's Wide			
	c- Minimum 180.25 Inches long Flat bed			
	d- Minimum 3/16" thickness for bed			
	e- And minimum 24.75 Inches of space for attachment of Hydraulic Loader Crane on the Rear of the Truck			
	f- (2) Storage Compartments Mounted to the underside of the Flat Bed Positioned to the front of the Flat Bed. One mounted on the Driver side One mounted on Passenger side			

State of Nebraska
 Technical Specification Sheet
 6914 OF Attachment A 1.0

	<p>Length:24" Minimum, 20" Depth minimum Each toolbox will hold 500 lbs of weight.</p> <p>(See Attachment E for visual example.)</p>			
	<p>g- Headache Rack Mounted to the front portion of the Flat bed directly behind the cab. Headache Rack can have two wings like in attachment D or can have single wing on the passenger side.</p> <p>See attachment E for Visual Example</p>			
	<p>h- Metal guardrails to shipped loose. To be attached by department after delivery of truck for storage of 1000lb weights.</p> <p>See attachment C for Specs</p>			
	<p>i- At the Rear of the Flat bed need to have a minimum 6.5 Inches by 24.75 Inches Torsion Frame for mounting of the Hydraulic Loader Crane</p>			
	<p>j- Metal Rock Gard with hardware to attach mudflap Mounted on the underside of the Flatbed Directly behind rear tire</p> <p>See Attachment D/E for Example</p>			

State of Nebraska
 Technical Specification Sheet
 6914 OF Attachment A 1.0

	<p>k- Side Signal Lights Need to meet DOT Standards</p> <p>Work with Agency Contact for exact specifications at time of build.</p>			
	<p>Rear Bumper and Lighting</p> <p>Work with Agency Contact at time of build.</p> <p>See Attachment D/E for example or Attachment E for Specs Bottom of receiver in Attachment E sits 20" off ground.</p>			
4	Hydraulic Loader Crane			
	<p>a- Max lifting Moment Minimum: 82,000 LBS</p>			
	<p>b- Max Lifting Capacity Minimum: 12,000 LBS</p>			
11	<p>c- Hydraulic Outreach Minimum: 26 Feet</p>			
12	d- Radio Remote Control.			
13	<p>e- Hydraulic operated Stability Points On the left and right side of the Vehicle</p>			
14	<p>f- See Attachment B for Dimensional Specification Must meet these Specification or be an Approved Equivalent. Would like Hydraulic Tank mounted on the rear next to crane to allow for two toolboxes mentioned above.</p>			
15	g- See Attachments D/E for examples.			

State of Nebraska
Technical Specification Sheet
6914 OF Attachment A 1.0

Base Price \$

Notes:

Contractor Information

Contractor:
Name:
Phone:
Address: